

NOTE:

1. CABLE: UL2725 USB 2.0 REV CABLE.(28AWG*1PAIR+ 20AWG*2C),AL-FOIL AND BRAID SHIELDED(A-MALLOY) WITH A DRAIN WIRE(BARE COPPER),PVC JACKET BLACK OD:4.8±0.15MM.
2. CONNECTOR:P1:USB A TYPE MALE,SOLDER TYPE,WHITE INSULATION, GOLD PLATED CONTACTS, GOLD PLATED SHELL. P2:USB B TYPE MALE,SOLDER TYPE,WHITE PBT INSULATION, GOLD PLATED CONTACTS, GOLD PLATED SHELL.
3. HOOD: MOLDED 45P BLACK PVC.
4. TESTING:100% ELECTRICAL TESTING.

PIN OUT

P1 ——— P2

20AWG	1	—————	1	RED
28AWG	2	—————	2	WHITE
28AWG	3	—————	3	GREEN
20AWG	4	—————	4	BLACK
	SHELL	—————	SHELL	(DRAIN)




CHART:

P/N	XX(FT)	L(MM)	TOLERANCE(MM)
USB2-AMBM-03	03	914	+50/-0
USB2-AMBM-06	06	1829	+75/-0
USB2-AMBM-10	10	3048	+75/-0

NET MECHANISM Corp www.cabling-ol.net			
SCALE	NONE		REV
UNIT	MM		B
SHEET	1/1	DWG NO.	
DATE	12/20/11		
TITLE USB A/M TO USB B/M 2.0			
PART NO. USB2-AMBM-XX			